

CLAMPMETER

Features

3 1/2 digit display

Frequency measuring range

Max test voltage 600V AC & DC

Max test current 400A AC

Diode test – On/Off buzzer – Data hold – RMS

Specification

DC Voltage	Range	200mV/2V/20V/200V/600V
	Accuracy	$\pm(0.8\%+1)$
AC Voltage	Range	2V/20V/200V/600V
	Accuracy	$\pm(1.2\%+5)$
AC Current	Range	2A/20A/200A/400A
	Accuracy	$\pm(1.5\%+5)$
Resistance	Range	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω
	Accuracy	$\pm(1\%+2)$
Input Resistance	>10M Ω	
Tested wire $\varnothing$	26mm	
Max display	1999	
Power supply	9V	
Weight	220g	
Dimensions	210 x 75.6 x 30mm	



MULTIMETER 33A (4 digits)

Specification

DC Voltage	Range	400mV/4V/400V/500V
	Accuracy	$\pm(0.8\% +1)$
AC Voltage	Range	4V/40V/400V/500V
	Accuracy	$\pm(1.2\% +3)$
DC Current	Range	400 μ A/4000 μ A/40mA/400mA/4A/10A
	Accuracy	$\pm(1\%+2)$
AC Current	Range	400 μ A/4000 μ A/40mA/400mA/4A/10A
	Accuracy	$\pm(1.5\%+5)$
Resistance	Range	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω
	Accuracy	$\pm(1\%+2)$
Auto ranging	Yes	
Diode	Yes	
Continuity buzzer	Yes	
Transistor test	Yes	
Input impedance	10M Ω	
Max display	3999	
Power	1.5V battery	
LCD display	48 x 16mm	
Weight	156g	
Size	490 x 73 x 315mm	

