

LCR METER

Features

Hand held and low consumption
Data Hold function

Specification	
Test Frequencies	100H, 1kHz
Measurement range and accuracy	L
	200uH/±(1.5%+5d)
	2mH/20mH/200mH/±(2%+5d)
	2H/±(3%+5d)
	20H/±(5%+15d)
	200H/±(5%+15d)
	C
	20pF/±(1.5%+5d)
	2nF/±(1%+5d)
	2μF/20μF/200 μF/±(1%+5d)
	100020μF/only for reference
	R
	20Ω/±(0.5%+10d)
	2kΩ/20kΩ/200kΩ/2MΩ/±(0.2%+1d)
	200MΩ/±(1%+5d)
Measurement speed	3 times /sec
Power Supply	9V Battery
Dimensions WxHxD	88 x 180 x 45mm
Weight	450g with battery



“Megger” INSULATION CONTINUITY TESTER DIT 5104

Features

Multi test voltage
Auto range on insulation
LCD Background light
Data Hold
LED indicator ON
Low battery warning
Function Display
AC Voltage Test

Specification	
Test Voltage	250/500/1000/2500
Insulation Resistance	0.1MΩ – 20GΩ
Accuracy	±(3%Rdg + 5 digits)
Resolution	0.01MΩ
AC Voltage Test	600VAC
Power Source	1.5 Alkaline Battery (AA) x 8
Dimensions	190 x 75 x 155mm
Weight	900gm
Accessories	Test Leads – Carry case

